

SIZE	STANDARD	CLASS	FLANGE DIAMETER		BOLT HOLE P.C.D.		BOLT HOLE DIAMETER		FLANGE THICKNESS		RAISED FACE DIAMETER		RAISED FACE HEIGHT		No. OF BOLTS N
			D		P		d		t		R		f		
			ins	mm	ins	mm	ins	mm	ins	mm	ins	mm	ins	mm	
24" 600mm	ASME B16.5	150	32	813	29 1/2	749	1 3/8	35	1 7/8	48	27 1/4	692	1/16	1.6	20
		300	36	914	32	813	1 5/8	41	2 3/4	70					24
		400					1 7/8	48	3	76			1/4	6.4	20
		900	41	1041	35 1/2	902	2 5/8	67	5 1/2	140					
	BS EN 1092/1 (PN)	16	33 1/16	840	30 5/16	770	1 7/16	36	1 9/16	54	28 9/16	725	3/16	5	20
		25	33 1/4	845			1 9/16	39	1 13/16	58	28 3/8	720			
		40	35 1/16	890	31 5/16	795	1 7/8	48	2 3/8	60	28 15/16	735			
	BS 10	E	32 1/2	826	29 3/4	756	1 1/4	32	1 1/2	38	27 1/2	699	1/16	1.6	16
		F	33 1/2	851	30 3/4	781	1 3/8	35	1 5/8	41					24
		H							2 1/4	57					
		J					1 1/2	38	2 3/4	70					